

Product information

megol Gasmotorenoel Synth SAE 40



Description

Fully synthetic gas motor oil based on polyalphaolefins and low-ash active agents. Prevents oil-related deposits in the combustion chambers to the greatest possible extent and allows extended oil change intervals. Can be used for high-load gas engines in natural gas, sewage gas and landfill gas operation with and without catalytic converter equipment. Characterized by very good detergent-dispersant capacity, very high resistance to oxidation, sufficient protection against nitration, high wear protection, medium ash content and medium alkalinity. The specifications and instructions from the assembly or machine manufacturer must be followed.



Available pack sizes

20 l Canister plastic

Part no. 8703
D-GB

200 l Drum sheet metal

Part no. 8763
D-GB

Characteristic data

Viscosity at 40 °C	88 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	13,3 mm ² /s ASTM D 7042-04
Viscosity at -25 °C	<7000 mPas DIN 51377
Viscosity index	152 DIN ISO 2909
Density at 15 °C	0,850 g/cm ³ DIN 51757
Flash point	254 °C DIN ISO 2592
Pour point	-36 °C DIN ISO 3016
Total base number	5,5 mg KOH/g DIN ISO 3771
Sulfate ash	0,5 g/100g DIN 51575
SAE class (engine oils)	10W-40 SAE J300