

# Product information

## Meguin Heissdampf Zylinderöel ZB 1000



### Description

Pure mineral oil primarily used to lubricate the sliding parts of steam engines that are in contact with steam and whose steam temperatures do not exceed 325 °C. Also suitable as a high viscosity lubricating oil for lubrication points with feed-through lubrication systems.

Specifications:

Lubricating oil ZB DIN 51510



### Characteristic data

|                     |   |
|---------------------|---|
| ISO viscosity class | VG 1000<br>DIN 51519                      |
| Density at 15 °C    | 0,900 g/cm <sup>3</sup><br>DIN 51757      |
| Viscosity at 40 °C  | 1000 mm <sup>2</sup> /s<br>ASTM D 7042-04 |
| Viscosity at 100 °C | 53,0 mm <sup>2</sup> /s<br>ASTM D 7042-04 |
| Viscosity index     | 100<br>DIN ISO 2909                       |
| Pour point          | -12 °C<br>DIN ISO 3016                    |
| Flash point         | 280 °C<br>DIN ISO 2592                    |
| Oxide ash           | 0,1 g/100g<br>DIN EN ISO 6245             |
| Color number (ASTM) | L 4,0<br>DIN ISO 2049                     |

### Available pack sizes

200 l Drum sheet metal

Part no. 8762  
D-GB