

Garden Winter Equipment Oil 5W-30

Description

Multigrade motor oil for year-round use. Exceeds the requirements of well-known engine manufacturers such as Briggs & Stratton, Honda and Tecumseh. Selected base oils based on synthetic technology and a higher additive content guarantee optimum lubrication and engine cleanliness, even under difficult operating conditions.

Properties

- no harmful effects on catalytic converters
- high resistance to aging
- low evaporation loss
- miscible with all commercially available motor oils
- very good dispersion properties
- universal application
- high wear resistance

Specifications and approvals:

ACEA C3 • API SN

Technical data

SAE class (engine oils)	5W-30 SAE J300
Density at 15 °C	0,850 g/cm ³ DIN 51757
Viscosity at 40 °C	68,9 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	12,0 mm ² /s ASTM D 7042-04
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -30°C (CCS)	<= 6600 mPas ASTM D5293
Viscosity index	172 DIN ISO 2909
HTHS at 150°C	>= 3,5 mPas ASTM D5481
Pour point	-39 °C DIN ISO 3016
Evaporation loss (Noack)	10,0 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	7,4 mg KOH/g DIN ISO 3771
Sulfate ash	<= 0,8 g/100g DIN 51575



Technical data

Color number (ASTM)	2,5
	DIN ISO 2049

Areas of application

For 4-stroke engines in lawn mowers, emergency power units, riding mowers, chippers, rotary tillers or motor hoes, scarifiers, string trimmers, high-pressure cleaners, snow blowers, etc.

Application

The specifications and instructions from the assembly or equipment manufacturer must be followed.

Available pack sizes

1 l Can plastic	1279
	D

Our information is based on thorough research and may be considered reliable, although not legally binding.