

Motorbike 4T Synth 10W-50 Offroad Race

Description

Fully synthetic high-performance motor oil. Ensures maximum performance and protection of the engine under all operating conditions. Optimum lubrication, outstanding engine cleanliness, excellent friction and minimum wear are just as much taken for granted as gentle clutch engagement and disengagement and gear shifting. That makes a big difference to driving enjoyment! Tested on engines with catalytic converters. Tested on racing machines.

Properties

- outstanding engine cleanliness
- especially suitable for wet clutches
- guarantees low oil consumption
- high shear stability
- excellent wear protection
- high resistance to aging
- optimum lubrication in extreme operating conditions

Specifications and approvals:

API SN Plus • JASO MA2

Technical data

| | |
|--------------------------|---|
| SAE class (engine oils) | 10W-50 SAE J300 |
| Density at 15 °C | 0,850 g/cm ³ DIN 51757 |
| Viscosity at 40 °C | 124 mm ² /s ASTM D 7042-04 |
| Viscosity at 100 °C | 18,5 mm ² /s ASTM D 7042-04 |
| Viscosity at -30°C (MRV) | < 60000 mPas ASTM D 4684 |
| Viscosity index | 165 DIN ISO 2909 |
| Viscosity at -25°C (CCS) | <= 7000 mPas ASTM D 5293 |
| Pour point | -39 °C DIN ISO 3016 |
| Evaporation loss (Noack) | 4,5 % CEC-L-40-A-93 |
| Flash point | 230 °C DIN ISO 2592 |
| Total base number | 7,0 mg KOH/g DIN ISO 3771 |
| Sulfate ash | 0,8 g/100g DIN 51575 |
| Color number (ASTM) | L 2,0 DIN 51578 |



Areas of application

Specially developed for air and water-cooled 4-stroke engines exposed to extreme loads off-road. For sporting applications. Suitable for Enduro and motocross motorbikes, quads, SxS and snowmobiles with and without a wet clutch.

Application

The operating instructions of the engine manufacturers must be followed.

Note: Optimum effectiveness only when the product is used on its own (i.e. no mixing).

Available pack sizes

| | |
|-----------------------|-----------------|
| 1 l Canister plastic | 3051 BOOKLET |
| 1 l Canister plastic | 1752 JP |
| 4 l Canister plastic | 3052 BOOKLET |
| 20 l Canister plastic | 21340 D-GB |

Our information is based on thorough research and may be considered reliable, although not legally binding.