

## Motorbike 2T Offroad

### Description

Part synthetic high-performance 2-stroke motor oil. Ensures optimum performance and protection of the engine in all operating conditions. Reliable lubrication, best engine cleanliness, excellent friction and minimum wear as well as low smoke.

### Properties

- guarantees clean spark plugs
- burns ash-free
- self mixing
- good corrosion protection
- residue-free combustion
- very wear resistant

### Specifications and approvals:

API TC • ISO L-EGC • JASO FC • TISI (Thailand International Standards Institute)

### Technical data

Density at 59 °F	0,865 g/cm <sup>3</sup> DIN 51757
Viscosity at 104 °F	59,5 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 212°F	9,1 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity index	130 DIN ISO 2909
Pour point	-11 °F DIN ISO 3016
Flash point	230 °F DIN ISO 2592
Total base number	1,1 mg KOH/g DIN ISO 3771
Sulfate ash	0,06 g/100g DIN 51575
Color / appearance	rot / red

### Areas of application

For air or water cooled 2-stroke gasoline engines where an oil according to current product specifications is required or recommended. Self-mixing. Pre-mix applications up to 1:50 ratio and according to the manufacturers instructions.

### Application

Observe the manufacturers instructions! Optimum effectiveness only when the product is used in undiluted form.



### Comment

**WARNING:** Cancer- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### Available pack sizes

1 l Canister plastic	20182 USA AND CANADA (-EN-F-)
4 l Canister plastic	20184 USA AND CANADA (-EN-F-)

**Our information is based on thorough research and may be considered reliable, although not legally binding.**