

Product information

Motorbike 2T Synth Offroad Race

PI 20/19/08/2019



Description

Fully synthetic high-performance motor oil. Ensures maximum performance and protection of the engine under all operating conditions. Optimum lubrication, outstanding engine cleanliness, excellent friction and minimum wear are just as much taken for granted as low smoke emissions. That makes a big difference to driving enjoyment! Tested on engines with catalytic converters. Tested on racing machines.

Properties

- high wear resistance
- prevents the build-up of deposits
- residue-free combustion
- high thermal stability
- good corrosion protection
- self mixing

Specifications and approvals:

API TC • Husqvarna • ISO L-EGD • JASO FD

Technical data

Density at 59 °F	0,875 g/cm ³ DIN 51757
Viscosity at 104 °F	50 mm ² /s ASTM D 7042-04
Viscosity at 212°F	9,1 mm ² /s ASTM D 7042-04
Viscosity index	165 DIN ISO 2909
Pour point	-54 °F DIN ISO 3016
Flash point	212 °F DIN ISO 2592
Total base number	2,3 mg KOH/g DIN ISO 3771
Sulfate ash	0,15 g/100g DIN 51575
Color / appearance	rot

Areas of application

Specially developed for air and water-cooled 2-stroke engines exposed to extreme loads off-road. For sporting applications. Suitable for Enduro and motocross motorbikes, quads, SxS and snowmobiles with separate and mixture lubrication. Self-mixing. Mixing ratio up to 1:100 in accordance with the operating instructions.



Application

For mixture lubrication, pour the contents of the can into the fuel tank and top up the fuel according to the mixing ratio. Mixing takes place automatically. For separate lubrication, pour the contents of the can into the oil tank. Oil is mixed with fuel via the metering device.

Comment

 **WARNING:** Cancer- www.P65Warnings.ca.gov

Available pack sizes

1 l Canister plastic	20178 USA AND CANADA (-EN-F-)
4 l Canister plastic	20180 USA AND CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.