

Product information

Motorbike Gasoline Stabilizer

PI 36/11/01/2021



Description

Preserves fuel against premature aging and oxidation during long term storage. Prevents corrosion in fuel system and increases operational reliability of 2- and 4-stroke engines in motor scooters, ATVs, snowmobiles etc. during long-term storage.

Properties

- has a lasting effect
- increases operational reliability
- simple to use
- tested for the use with catalytic converters
- cost-effective due to exact dosage
- protects fuel against oxidation and aging

Technical data

Base	Additiv-Kombination in Trägerflüssigkeit / additive mixture in carrier liquid
Color / appearance	blau / blue
Odor	charakteristisch / characteristic
Form	flüssig / liquid
Density at 59 °F	0,822 g/cm ³
Hazard class as per German VbF	A III
Flash point	>142 °F
Viscosity at 104 °F	<7 mm ² /s

Areas of application

Suitable for all 2- stroke and 4-stroke gasoline engines. Safe with catalytic converters.

Application

Use 25 mL dosage with 5 Liters (1.3 gal.) of fuel. Add to fuel and let the engine idle for approx. 10 minutes.

Comment

 **WARNING:** Cancer - www.P65Warnings.ca.gov



Available pack sizes

250 ml Dispensing bottle plastic	20052 USA (-EN-)
250 ml Dispensing bottle plastic	22102 CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.