

Product information

Motorbike Speed Additive

PI 35/05/12/2019



Description

Acceleration improving, cleaning, dispersing and material-protecting properties. The product has been formulated using state-of-the-art additive and fuel technologies in accordance with the requirements of today's engines, fuels and operating conditions. Ensures increased driving pleasure due to optimized performance. The engine runs smoother and more efficient.

Properties

- increasing performance
- improves the acceleration
- protects fuel against oxidation and aging
- cleans the fuel system
- prevents corrosion in the fuel system
- prevents carburetor icing
- increases operational reliability

Available pack sizes

150 ml Can sheet metal 20108
USA (-EN-)

Our information is based on thorough research and may be considered reliable, although not legally binding.

Technical data

Base	Additiv-Kombination in Trägerflüssigkeit / additive mixture in carrier fluid
Color / appearance	gelb, klar / yellow, clear
Odor	charakteristisch / characteristic
Form	flüssig / liquid
Viscosity at 104 °F	<7 mm ² /s
Density at 68 °F	0,814 g/cm ³
Hazard class as per German VbF	A III
Flash point	>142 °F

Areas of application

Added to the fuel of all 4-stroke and 2-stroke gasoline engines, suitable for carburetor and injection systems.

Application

Add into the fuel tank. For optimum effect, add every time you refuel. Fully compatible with all grades of gasoline fuel. Contents of can are sufficient to treat up to 20 liters (5.2 gal.) of fuel. Minimum fuel filling of 15 liters (4 gal.) is requested for optimum product performance. Product is self mixing with fuel.

Comment

 **WARNING:** Cancer- www.P65Warnings.ca.gov