

Product information

Pro-Line PTFE Powder Spray

PI 18/20/05/2019



Description

Grease-free lubricant and release agent based on PTFE (Teflon or polytetrafluoroethylene). Eliminates squeaking, creaking and stiffness and offers long-lasting protection against wear. The dry lubricant does not attract dirt or dust.

Properties

- high chemical resistance
- free of oil, grease and silicones
- easy to use
- extremely low friction
- eliminates squeaks
- suitable for care, protection and insulation
- broad operating temperature range

Technical data

Color / appearance	weiß / white
Base	PTFE
Density	0,58 g/ml
Operating temperature range	-40 bis +250 / -40 to +250 °C
Propellant	Propan, Butan / propane, butane
Flash point	-60 °C
Form	flüssig / liquid
Odor	charakteristisch / characteristic

Areas of application

For optimal lubrication of moving parts such as slide rails, joints, locking parts, belt mechanisms, etc. As a separating agent or to eliminate noise of coverings for almost all materials. Particularly suitable in areas where lubricants containing oil and silicone impair the finishing work.

Application

The surface to be treated must be free of grease, clean and dry. Apply thin coats and leave to dry in between treatments. The fold-out capillary tube ensures precision spraying. With the capillary tube folded in, large areas are sprayed. Also sprays when inverted.



Available pack sizes

400 ml Can aerosol	7384 D-GB-I-E-P
400 ml Can aerosol	20672 D-NL-F-GR-RUS

Our information is based on thorough research and may be considered reliable, although not legally binding.