

Product information

Pro-Line Electronic Spray

PI 17/20/05/2019



Description

Fully synthetic Electronic Spray that is compatible with plastics for the cleaning and care of contaminated electrical parts. Protects the electronic parts against corrosion by driving out moisture and water. Infiltrates the oxide and sulfide layers, thereby reducing contact resistance, protecting the electronic parts and ensuring operational reliability. No adverse effects on plastic and rubber components. The quick-drying formula does not leave residues and is silicone-free.

Properties

- reduces contact resistance
- leaves no residues
- neutral behavior in contact with rubber and plastics
- silicone-free
- also suitable for overhead work
- penetrates and drives out moisture
- good corrosion protection
- cleans contaminated contacts

Technical data

Color / appearance	blau / blue
Base	Syntheseöl / synthetic oil
Density at 20 °C	0,85 g/cm ³ DIN 51 757
Pour point	-53 °C DIN ISO 3016
Flash point	201 °C DIN ISO 2592
Viscosity index	145
Evaporation loss (Noack)	2,1 Gew.-% DIN ISO 2909
Water content	40 ppm $\Omega \cdot \text{cm}$ DIN 51 581
Neutralization number	0,03 mg KOH/g DIN 51 777 T 1
Copper corrosion	0-1 DIN 51 809
Specific electrical volume resistance at 20 °C	$1,6 \cdot 10^9 \Omega \cdot \text{cm}$
Odor	charakteristisch / characteristic
Form	flüssig / liquid
Viscosity at 40 °C	>7 mm ² /s



Areas of application

Used for the maintenance, care, cleaning and protection of all electrical components on the motor vehicle such as plug and terminal connections, lamp sockets, cable distribution boxes, switch elements, relays, ignition distributors, contact breakers, starters, alternators, fuses, battery terminals and antennae and for the lubrication of fine mechanical parts.

Application

Spray electric components before assembly, then assemble. With severely corroded contacts, allow to act for longer. Rub off loosened corrosion residues with a cloth or brush. The fold-out capillary tube ensures precision spraying. With the capillary tube folded in, large areas are sprayed. Also sprays when inverted.

Note: After spraying on, allow a flash-off time of 10 min before connecting the component to a power supply.

Available pack sizes

400 ml Can aerosol	7386 D-GB-I-E-P
400 ml Can aerosol	9913 GB-DK-FIN-N-S
400 ml Can aerosol	20674 D-NL-F-GR-RUS

Our information is based on thorough research and may be considered reliable, although not legally binding.