

## Cable Grease (Spray)

### Description

High quality lubricant for the lubrication and preservation of wire cables. Excellent corrosion protection enables the use of the product for cavity sealing and underfloor protection in the automotive sector.

### Properties

- excellent corrosion protection
- drives out moisture
- has a lasting effect
- excellent penetration action
- highest load-carrying capacity
- optimum effectiveness when the product is used unmixed
- no aromatic hydrocarbons
- high bond strength

### Technical data

Density at 15 °C	0,85 g/cm <sup>3</sup>
Color / appearance	braun / brown
Flash point	-60 °C
Dropping point	> 85 °C
Base	Additive, Polymere / additives, polymers
Viscosity at 40 °C	22 mm <sup>2</sup> /s
Form	aerosol, flüssig / aerosol, liquid
Odor	charakteristisch / characteristic
Density	0,731 g/cm <sup>3</sup>
Shelf life in original sealed container	30 months
Recommended storage temperature	10 - 30 °C

### Areas of application

For the preventive lubrication, relubrication and preservation of wire cables. Ideally suited for the cavity sealing and underfloor protection of vehicles.

### Application

Cable Grease is applied as an aerosol by spraying onto the cables. An adherent film is formed after the solvent evaporates.

### Comment

Shake before using. After use, clear spray nozzle by inverting the can and spraying until only the propellant emerges.



### Available pack sizes

500 ml Can aerosol	6135
	D-GB-I-E

**Our information is based on thorough research and may be considered reliable, although not legally binding.**