

LM 48 Spray Paste

Description

Sprayable mineral oil-based tungsten disulfide assembly paste containing selected solid lubricants. Is suitable for the highest requirements thanks to the special preparation methods. Contains a synergistically active solid lubricant system with a zinc sulfide, graphite, fluorides and tungsten disulfide base.

Properties

- extremely low friction
- outstandingly adherent
- outstanding emergency-running properties
- good corrosion protection
- high wear resistance
- universal application
- easy to use

Technical data

Color / appearance	nicht bestimmt
Base	Mineralöl / mineral oil
Additives	MoS ₂ 33, Graphit 6 %
Propellant	Propan, Butan / propane, butane
Operating temperature range	-35 bis +450 / -35 to +450 °C
Pressfit test (no stick slip)	0,12 µ
Screw test thread friction	0,09 µ
Odor	charakteristisch / characteristic
Form	flüssig, aerosol / liquid, aerosol
Density	0,71 g/ml

Areas of application

For assembly, repair and maintenance in all technical areas. For basic lubrication and preventing running-in damage as well as lifetime lubrication of bearings, joints and small components. Specially suitable for surfaces and components with complex shapes.

Application

Shake can vigorously before use. Spray the product thinly and uniformly onto clean surfaces. Avoid excess for economical reasons. After use, clear spray nozzle (hold can with spray head upside down) by spraying until only pure propellant emerges.



Available pack sizes

300 ml Can aerosol	3045
	D-GB-I-E-P

Our information is based on thorough research and may be considered reliable, although not legally binding.