

Motorbike HD Synth 20W-50 Street

Description

Fully synthetic motor oil tailored for use in air and water-cooled four-stroke motorbike engines, especially suitable for Harley Davidsons. Selected base oils and high-quality additive components ensure optimum lubrication, outstanding engine cleanliness and excellent friction in all operating conditions. Exceptionally well-suited for use with or without a wet clutch.

Properties

- stable to ageing and stable viscosity
- excellent wear resistance
- outstanding corrosion protection
- high engine cleanliness
- outstanding high temperature stability

Specifications and approvals:

API SN Plus • JASO MA2

Technical data

| | |
|--------------------------|--|
| SAE class (engine oils) | 20W-50 SAE J300 |
| Density at 15 °C | 0,850 g/cm ³ DIN 51757 |
| Viscosity at 40 °C | 140,0 mm ² /s ASTM D 7042-04 |
| Viscosity at 100 °C | 20,0 mm ² /s ASTM D 7042-04 |
| Viscosity at -20°C (MRV) | < 60000 mPas ASTM D4684 |
| Viscosity at -15°C (CCS) | <= 9500 mPas ASTM D5293 |
| Viscosity index | 165 DIN ISO 2909 |
| HTHS at 150°C | >= 3,7 mPas ASTM D5481 |
| Pour point | -36 °C DIN ISO 3016 |
| Evaporation loss (Noack) | 4,0 % CEC-L-40-A-93 |
| Flash point | 250 °C DIN ISO 2592 |
| Total base number | 7,0 mg KOH/g DIN ISO 3771 |
| Sulfate ash | 0,8 g/100g DIN 51575 |
| Color number (ASTM) | L 2,0 DIN ISO 2049 |



Areas of application

Developed for year-round use in road, off-road and racing machines operated under normal to extreme conditions, including many Harley Davidson V-Twin engines that require a synthetic motor oil of viscosity 20W-50. Exceptionally well-suited for use with or without a wet clutch.

Application

The operating instructions of the vehicle manufacturers must be followed. Note: Optimum effectiveness only when the product is used on its own (i.e. no mixing).

Available pack sizes

| | |
|------------------------|-----------------|
| 1 l Canister plastic | 3816 BOOKLET |
| 1 l Canister plastic | 20858 JP |
| 4 l Canister plastic | 3817 BOOKLET |
| 20 l Canister plastic | 3818 D-GB |
| 60 l Drum sheet metal | 3819 D-GB |
| 205 l Drum sheet metal | 3820 D-GB |

Our information is based on thorough research and may be considered reliable, although not legally binding.