

Product information

Motorbike Speed Shooter

PI 32/30/01/2020



Description

State-of-the-art, ash-free combination of agents with acceleration-enhancing, cleaning, dispersing and material-protecting properties. The product has been formulated using state-of-the-art additive and fuel technologies in accordance with the requirements of today's engines, fuels and running conditions. Ensures increased driving enjoyment due to optimized performance. The engine starts easier and also runs smoother.

Properties

- good corrosion protection
- residue-free combustion
- guarantees optimum combustion
- improves the acceleration
- removes deposits from entire fuel system
- highly economical
- prevents carburetor icing
- higher performance gain

Technical data

Base	Additiv-Kombination in Trägerflüssigkeit / additive mixture in carrier fluid
Color / appearance	gelb, klar / yellow, clear
Odor	charakteristisch / characteristic
Form	flüssig / liquid
Viscosity at 40 °C	<7 mm ² /s
Density at 20 °C	0,814 g/cm ³
Hazard class as per German VbF	A III
Flash point	>61 °C

Areas of application

For 2-stroke and 4-stroke gasoline engines (aspirated and injection).

Application

Add to the fuel tank. For the optimum effect, add every time you refuel. Fully compatible with all gasoline grades. 80 ml is sufficient for up to 10 liters of fuel.

Available pack sizes

80 ml Can sheet metal	7820 GB
80 ml Can sheet metal	8265 JP
80 ml Can sheet metal	7915 VN
80 ml Can sheet metal	7823 TR
80 ml Can sheet metal	20596 DK
80 ml Can sheet metal	20581 S
80 ml Can sheet metal	20592 BG
80 ml Can sheet metal	20577 FIN
80 ml Can sheet metal	20584 IR
80 ml Can sheet metal	20585 ID
80 ml Can sheet metal	20559 H

Our information is based on thorough research and may be considered reliable, although not legally binding.