

## Marine Winch Grease

### Description

Synthetic high-performance grease with PTFE solid lubricants specially developed for all kinds of winching and hoisting applications. The solid lubricant provides the ultimate in wear protection and reduces friction. Resistant to seawater and freshwater with excellent adhesive properties. Does not contain resins or acids.

### Properties

- excellent high-pressure and wear protection properties
- outstandingly adherent
- outstanding sea and fresh water resistance
- ensures a long service life

### Technical data

Brief description	KHCF1N-35
Saponification type	gel
Base	Syntheseöl / synthetic oil
Operating temperature range	-95 bis 302 °F
Color / appearance	weiß / white
NLGI number	1 DIN 51 818
Dropping point	ohne/without DIN ISO 2176
Base oil viscosity 104 °F	440 mm <sup>2</sup> /s DIN 51 562
Water resistance	0 DIN 51807

### Areas of application

Ideally suited for winching and hoisting applications with non-ferrous metal pairings and plastic/metal pairings. Powerful adhesive properties and neutral in respect of harmful environmental factors.

### Application

Before treating, the surfaces must be clean and free from residues, dirt and moisture.



### Available pack sizes

100 g Tube plastic	20524
	USA AND CANADA (-EN-F-)

**Our information is based on thorough research and may be considered reliable, although not legally binding.**