

# Product information

## Marine Super Diesel Additiv

PI 20/29/08/2019



### Description

A combination of agents which cleans, disperses, protects components and boosts the cetane number. The enhanced ignition performance improves the combustion of the fuel which in turn reduces emissions. The high proportion of corrosion protection additives reliably protects the entire fuel system from the formation of rust and corrosion. Due to its outstanding cleaning properties, the components remain clean and deposits are removed. The engine performance remains at a consistently high level.

### Properties

- boosts the cetane number
- keeps the fuel system clean
- optimizes engine performance
- keeps injection nozzles clean
- guarantees low fuel consumption
- high wear resistance
- prevents the build-up of deposits
- increases the lubricating effect
- prevents seizing and the injector needles from gumming up

### Technical data

Base	Additiv-Kombination in Trägerflüssigkeit / additive mixture in carrier fluid
Color / appearance	gelb-braun / yellowish brown
Density at 15 °C	0,87 g/cm <sup>3</sup>
Hazard class as per German VbF	A III
Flash point	63 °C
Pour point	-36 °C

### Areas of application

For all diesel engines in the marine sector, including pumped-jet and common rail injection systems. Fully compatible with all conventional diesel and biodiesel fuels.

### Application

500 ml is sufficient for 250 l of fuel. Filling the dosage chamber (25 ml) once is sufficient for 12.5 l of fuel.

### Available pack sizes

500 ml Can sheet metal	25004 D-F-I-E-GR
500 ml Can sheet metal	25005 GB-DK-N-FIN-S-RUS
1 l Can sheet metal	25006 D-F-I-E-GR
1 l Can sheet metal	25007 GB-DK-N-FIN-S-RUS

**Our information is based on thorough research and may be considered reliable, although not legally binding.**