

Marine 2T Motor Oil

Description

High-performance 2-stroke motor oil based on selected base oils and specially formulated additives. Provides for reliable lubrication, engine reliability and outstanding protection against wear and corrosion. No uncontrolled ignition, low-fuming combustion. With TC-W3-level performance.

Properties

- high lubrication reliability
- very wear resistant
- prevents spontaneous ignition
- self mixing
- residue-free combustion

Specifications and approvals:

API TC • JASO FB • NMMA TC-W3®

Technical data

Viscosity at 104 °F	54,2 mm ² /s ASTM D 7042-04
Viscosity at 212°F	8,9 mm ² /s ASTM D 7042-04
Viscosity index	143 DIN ISO 2909
Density at 59 °F	0,880 g/cm ³ DIN 51757
Flash point	223 °F DIN ISO 2592
Pour point	-38 °F DIN ISO 3016
Total base number	9,8 mg KOH/g DIN ISO 3771
Sulfate ash	<0,02 g/100g DIN 51575
Color number (ASTM)	4,0 DIN ISO 2049

Areas of application

For air and water-cooled 2-stroke marine engines with separate and premix lubrication systems. Self-mixing. Please note that the mixture ratio specified by the manufacturer must be observed.

Application

Use as normal for 2-stroke oils for mixture and separate lubrication systems. Keep to the mixing ratios stipulated by the relevant engine manufacturer.



Our information is based on thorough research and may be considered reliable, although not legally binding.