

Product information

Special Tec V SAE 0W-20

PI 24/02/07/2021



Description

Fully synthetic superior, low friction motor oil. Developed specifically for use in various late model Volvo vehicles and also suitable for use in several other manufacturers vehicles. The low viscosity ensures excellent cold start behavior, improves engine efficiency and reduces fuel consumption. Use with extended oil change intervals as per manufacturer.

Properties

- reduces friction
- guarantees maximum performance
- saves fuel
- outstanding engine cleanliness
- excellent resistance to aging
- compatible for the use with turbochargers and catalytic converters

Specifications and approvals:

ACEA C5 • API SN • Volvo VCC RBS0-2AE

Technical data

SAE class (engine oils)	0W-20 SAE J300
Density at 59 °F	0,845 g/cm ³ DIN 51757
Viscosity at 104 °F	47,0 mm ² /s ASTM D 7042-04
Viscosity at 212°F	9,0 mm ² /s ASTM D 7042-04
Viscosity at -40 °F (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -31 °F (CCS)	≤ 6200 mPas ASTM D 5293
Viscosity index	175 DIN ISO 2909
HTHS at 302 °F	≥ 2,6 mPas ASTM D 5481
Pour point	-54 °F DIN ISO 3016
Evaporation loss (Noack)	13 % CEC-L-10-A-93
Flash point	446 °F DIN ISO 2592
Total base number	7,9 mg KOH/g DIN ISO 3771
Sulfate ash	< 0,9 % DIN 51575

Technical data

Color number (ASTM) L 3,0
DIN ISO 2049

Areas of application

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers.

Application

Observe the manufacturers instructions!

Available pack sizes

1 l Canister plastic	20198 USA AND CANADA (-EN-F-)
5 l Canister plastic	20200 USA AND CANADA (-EN-F-)
60 l Drum sheet metal	20355 USA AND CANADA (-EN-F-)
1000 l Container	22172 USA AND CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.