

## Marine ATF

### Description

Fully synthetic ATF oil specially developed for the marine sector. Offers increased corrosion protection and minimizes wear compared with conventional ATF oils. The high thermal stability and excellent protective properties give it optimum resistance to aging with maximum safety reserves. Compatible with all sealing materials.

### Properties

- optimum stability to aging
- excellent corrosion protection
- highest thermal stability
- universal application
- good material compatibility
- minimizes wear

### Specifications and approvals:

Dexron II D • Dexron II E • Dexron III G • Dexron III H  
• Dexron TASA (Typ A/Suffix A)

### LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Allison C4 • ZF TE-ML 02F • ZF TE-ML 03D • ZF TE-ML 04D • ZF TE-ML 11B • ZF TE-ML 14A • ZF TE-ML 14B

### Technical data

Density at 59 °F	0,845 g/cm <sup>3</sup> DIN 51757
Viscosity at 104 °F	36,0 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 212°F	7,5 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -40 °F (Brookfield)	<= 20000 mPas ASTM D 2983-09
Viscosity index	180 DIN ISO 2909
Pour point	-54 °F DIN ISO 3016
Flash point	428 °F DIN ISO 2592
Sulfate ash	0,10 g/100g DIN 51575
Scherstabilität, Viskosität bei 100°C nach 100 h	5,4 mm <sup>2</sup> /s DIN 51350-06-KRL/C
Color / appearance	rot



### Areas of application

For drives and transmissions such as reverse gears, power steering, control systems, trimming systems, hydrostatic transmission ratios and hydraulic and mechanical systems that require the use of an ATF oil. Cannot be used where GL4 or GL5 oils are specified.

### Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed.

### Available pack sizes

1 l Can plastic	20544 USA AND CANADA (-EN-F-)
-----------------	----------------------------------

**Our information is based on thorough research and may be considered reliable, although not legally binding.**