

Truck Series Complete Fuel System Cleaner

Description

Eliminates starting problems and noisy engine running. Ensures optimum atomization. Removes deposits on the injection nozzle, intake valve, and spark plug, and in the combustion chamber. Prevents new deposits forming. Cares for all parts of the gasoline injection system and protects the entire fuel system against corrosion. Optimizes emissions values and engine performance. Clean engines use less fuel and emit fewer pollutants.

Properties

- cleans the mixture preparation system as well as the intake valves and the combustion chamber
- improves performance
- prevents corrosion in the fuel system
- normalizes gasoline consumption and exhaust emissions values

Technical data

Base	Additiv-Kombination in Trägerflüssigkeit / additive mixture in liquid carrier
Color / appearance	hellgelb, klar / light yellow, clear
Regulation on Flammable Liquids Class (Germany)	A II
Flash point	>61 °C
Pour point	-45 °C
Form	flüssig / liquid
Odor	charakteristisch / characteristic
Viscosity at 40 °C	<7 mm ² /s
Density at 15 °C	0,765 g/cm ³

Areas of application

Suitable for all gasoline engines.

Application

Can is sufficient to treat up to 115 l of fuel. For optimum performance a minimum fill of 25 l is required. Add every 2,000 km before filling up.



Available pack sizes

500 ml Can sheet metal	20995
	GB-F-RUS-ARAB
500 ml Can sheet metal	21454
	GB-P

Our information is based on thorough research and may be considered reliable, although not legally binding.