

Truck Series Diesel Performance and Protectant

Description

Optimizes the combustion process and restores the original performance of the engine. Removes deposits in the diesel injection system and combustion chamber and prevents new deposits forming. Improves lubrication throughout the fuel system. Boosts the cetane number and improves the ignition capability of the diesel fuel. Protects against corrosion and wear. Optimizes emissions values and engine performance. Clean engines use less fuel and emit fewer pollutants.

Properties

- removes undesirable residues
- prevents the build-up of deposits
- protects expensive components against wear and corrosion
- increases smooth operation
- boosts the cetane number
- reduces pollutant emissions

Technical data

Base	Additiv-Kombination in Trägerflüssigkeit / additive mixture in liquid carrier
Color / appearance	hellbraun, klar / light brown, clear
Density at 15 °C	0,842 g/cm ³
Regulation on Flammable Liquids Class (Germany)	A III
Flash point	63 °C
Pour point	- 36 °C
Form	flüssig / liquid
Odor	charakteristisch / characteristic

Areas of application

Suitable for all diesel engines.

Application

Can is sufficient to treat up to 115 l of diesel fuel. For optimum performance a minimum fill of 25 l is required. Add every 2,000 km before filling up.



Available pack sizes

500 ml Can sheet metal 20997
GB-F-E-ARAB

Our information is based on thorough research and may be considered reliable, although not legally binding.