

Truck Series Diesel Performance and Protectant

Description

Optimizes the combustion process. The engine regains its original power.

- Removes deposits in the diesel injection system and in the combustion chamber and prevents new deposits forming.
- Increases the lubrication in the entire fuel system.
- Increases the cetane number and improves the ignitability of the diesel fuel.
- Ensures the engine runs smooth.
- Protects against corrosion and wear.
- Optimises the exhaust gas values and performance of the engine.
- Clean engines consume less fuel and emit less pollutants.

Properties

- removes undesirable residues
- prevents the build-up of deposits
- protects expensive components against wear and corrosion
- increases smooth operation
- boosts the cetane number
- reduces pollutant emissions

Technical data

Base	Additiv-Kombination in Trägerflüssigkeit / additive mixture in liquid carrier
Color / appearance	hellbraun, klar / light brown, clear
Density at 59 °F	0,842 g/cm ³
Regulation on Flammable Liquids Class (Germany)	A III
Flash point	145 °F
Pour point	- 97 °F
Form	flüssig / liquid
Odor	charakteristisch / characteristic

Areas of application

Suitable for all diesel engines.

Application

The can is sufficient for up to 150 liters (40 gal.) of diesel fuel. Effect lasts up to 2000 km (1200 miles). Minimum fuel filling of 25 liters (7 gal.) is requested for optimum product performance.



Comment

WARNING: Cancer - www.P65Warnings.ca.gov.

Available pack sizes

500 ml Can sheet metal 20254
USA (-EN-)

Our information is based on thorough research and may be considered reliable, although not legally binding.