

# Product information

## Marine Storage Fogging Oil

PI 3/01/12/2017



### Description

Long-term protection against corrosion on the surfaces of the combustion chamber such as cylinder walls, piston crowns and piston rings. Ensures smooth restarting after shutdown.

### Properties

- excellent corrosion protection
- high spreading rate
- has a lasting effect
- simple to use

### Technical data

Color / appearance	braun / brown
Propellant	Propan, Butan / propane, butane
Protects against corrosion	bestanden / approved DIN 51357/51358/51585
Odor	charakteristisch / characteristic
Form	flüssig / liquid
Density	0,7 g/l

### Areas of application

For the reliable long-term preservation of all 2-stroke and 4-stroke gasoline and diesel engines on boats and ships as well as assembly units and pumps.

### Application

The preservative is applied via the carburetor or access opening of spark plugs, injection nozzles or glow plugs.

#### 2-stroke engine

Remove the air filter. With the engine running at low revs, spray the preservative into the carburetor for 10-20 sec. Switch off the engine and remove the spark plugs. Spray the preservative into the cylinder for 5-10 sec (depending on the size of the cylinder). Turn the engine by hand.

#### 4-stroke engine

Remove spark plugs, injection nozzles or glow plugs and spray the preservative into the cylinder for 5-10 sec. (depending on the size of the cylinder). Turn the engine by hand or with a starter motor (without adding fuel). Refit the spark plugs, injection nozzles or glow plugs. The preservative does not need to be removed in order to restart the engine.



### Available pack sizes

300 ml Can aerosol	20544
	GB-F-E-USA-CAN

**Our information is based on thorough research and may be considered reliable, although not legally binding.**