

# Product information

PI 18/17/06/2020



## Motorbike 4T 5W-40 HC Scooter

### Description

High-performance motor oil based on synthetic technology. For maximum performance and protection of the engine under all operating conditions. Ensures optimum lubrication, outstanding engine cleanliness, excellent friction and minimum wear.

### Properties

- guarantees low oil consumption
- high shear stability
- high wear resistance
- optimum stability to aging
- optimum lubrication under all operating conditions
- outstanding engine cleanliness
- tested for the use with catalytic converters

### Specifications and approvals:

API SN PLUS • JASO MA2

**LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:**

Kymco • Piaggio

### Technical data

Viscosity SAE class	5W-40 SAE J300
Density at 15 °C	0,850 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	85,0 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	14,3 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -30°C (CCS)	<= 6600 mPas ASTM D 5293
Viscosity index	175 DIN ISO 2909
HTHS at 150°C	>= 3,5 mPas ASTM D 5481
Pour point	-36 mPas DIN ISO 2909
Evaporation loss (Noack)	11,0 % ASTM D 5800 B
Flash point	228 °C DIN ISO 2592
Total base number	7,0 mg KOH/g DIN ISO 3771



### Technical data

Sulfate ash	0,8 g/100g DIN 51575
Color number (ASTM)	L 2,0 DIN ISO 2049

### Areas of application

Developed for air and water-cooled 4-stroke engines exposed to normal to extreme operating conditions. For the sporty driver.

### Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed! Optimum effectiveness is only possible when the product is used unmixed.

### Available pack sizes

1 l Canister plastic	20829 BOOKLET
4 l Canister plastic	20830 BOOKLET
20 l Canister plastic	20831 D-GB

**Our information is based on thorough research and may be considered reliable, although not legally binding.**