

Classic Transmission Oil SAE 90

Description

Mineral-based transmission oil specially designed for classic vehicles and motorcycles. Provides a stable lubricating film and minimizes wear. Offers very good lubrication properties and optimum corrosion protection. Enables smooth gearshifting.

Properties

- minimizes wear
- reduces running noise
- good corrosion protection
- does not attack common sealing materials
- also suitable for classic motorcycles

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

API GL1 • API GL2 • API GL3 • Alfa Romeo • AMC • BMW • Jeep • Opel • Rolls-Royce • Volkswagen • Volvo

Technical data

SAE class (gear oils)	90 SAE J306
Density at 15 °C	0,880 g/cm ³ DIN 51757
Viscosity at 40 °C	181 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	16,5 mm ² /s ASTM D 7042-04
Viscosity index	95 DIN ISO 2909
Pour point	-24 °C DIN ISO 3016
Flash point	234 °C DIN ISO 2592
Color number (ASTM)	L 3,5 DIN ISO 2049

Areas of application

For manual transmissions of classic vehicles and motorcycles with a low load in which a transmission oil compliant with API GL1/GL2/GL3 is required.

Application

When selecting the product, note the viscosity class and specification stipulated by the transmission manufacturer. Mixable with all branded gear oils. Full effectiveness only achieved when the product is used on its own (i.e. no mixing).



Available pack sizes

1 l Can plastic	20816
	D-GB-I-E-P

Our information is based on thorough research and may be considered reliable, although not legally binding.