

Product information

Snowbike Motor Oil 0W-40

PI 10/24/02/2020



Description

Fully synthetic low-friction motor oil. Ensures the fastest oil penetration of the engine and optimum engine lubrication after the first turn of the engine even at very low temperatures. Has low viscosity and high shear resistance thanks to advanced additive technology. Reliably prevents deposits, reduces frictional losses of the engine and contributes to maximum wear reduction. Tested on engines with catalytic converters.

Properties

- excellent wear protection
- outstanding high temperature stability
- extremely low evaporation loss
- instant lubrication after cold start
- outstanding lubrication reliability
- optimum oil pressure under all operating conditions
- outstanding engine cleanliness
- tested for the use with catalytic converters

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

JASO MA2

Technical data

SAE class (engine oils)	0W-40 SAE J300
Density at 15 °C	0,845 g/cm ³ DIN 51757
Viscosity at 40 °C	76,5 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	13,7 mm ² /s ASTM D 7042-04
Viscosity at -35°C (CCS)	<6200 mPas ASTM D 5293
Viscosity index	185 DIN ISO 2909
Pour point	-42 °C DIN ISO 3016
Flash point	226 °C DIN ISO 2592
Evaporation loss (Noack)	13,0 % ASTM D 5800-08 Method B
Total base number	6,4 mg KOH/g DIN ISO 3771



Technical data

Color number (ASTM) L 2,0
DIN ISO 2049

Areas of application

Specially developed for the requirements of 4-stroke engines in snowbikes.

Application

The operating instructions of the snowbike manufacturers must be followed.

Available pack sizes

1 l Canister plastic	20356 USA AND CANADA (-EN-F-)
4 l Canister plastic	20358 USA AND CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.