

Product information

Anti-bacterial Diesel additive

PI 13/10/10/2019



Description

Highly active biocide with wide action spectrum against bacteria, yeasts and moulds. **Use biocides safely. Always read the label and product information before use.**

Properties

- keeps injection nozzles clean
- reduces pollutant emissions
- neutralizes acids
- eliminates diesel knocking
- active in preventing bacterial infestation
- decontaminates infested tank systems
- highly effective

Technical data

Base	Biozid, Detergent, Cetanzahlverbesserer / biocide, detergent and cetan number enhancer
Color / appearance	braun, klar / brown, clear
Density at 15 °C	0,923 g/cm ³
Viscosity at 40 °C	<7 mm ² /s
Flash point	>63-<100 °C
Regulation on Flammable Liquids Class (Germany)	A III
Shelf life in original sealed container	5 Jahre / 5 years
Odor	charakteristisch, characteristic
Form	flüssig / liquid

Areas of application

For preventive use in diesel-powered vehicles that have been decommissioned for a long time or are in low use such as construction machinery, commercial vehicles, mobile homes, passenger motor vehicles, in storage tanks or for disinfection of contaminated tank systems.

Application

Dosage 1:1000. One 25 ml measurement cup is sufficient for 25 litres of diesel fuel. For prevention, add the corresponding amount before filling the tank. For extreme bacteria and mould infestation with clogged filter, use it as a remedial shock treatment (dosage 1:200).



Available pack sizes

125 ml Can sheet metal	20940 GB-GR-I
1 l Can sheet metal	21317 D-GB-F-I-E-GR
1 l Can sheet metal	2368 GB-DK-FIN-N-S
5 l Canister plastic	21318 D-GB-E
60 l Drum sheet metal	21319 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.