

Product information

Marine Jet Ski Oil 10W-40

PI 6/10/03/2020



Description

High-performance motor oil based on synthetic technology. The special additive package ensures maximum engine performance and ideal wear protection. Guarantees the best possible lubrication, outstanding engine cleanliness and excellent friction values for wet clutches, even at high speeds. Satisfies or exceeds the requirements and specifications of the leading engine manufacturers.

Specifications and approvals:

API SN Plus • JASO MA2

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Honda • Kawasaki • SeaDoo • Suzuki • Yamaha

Technical data

SAE class (engine oils)	10W-40 SAE J300
Density at 15 °C	0,860 g/cm ³ DIN 51757
Viscosity at 40 °C	96,0 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,6 mm ² /s ASTM D 7042-04
Viscosity at -25°C (CCS)	<= 7000 mPas ASTM D 5293
Viscosity index	158 DIN ISO 2909
Pour point	-36 °C DIN ISO 3016
Evaporation loss (Noack)	10,0 % ASTM D 5800-08 Method B
Flash point	238 °C DIN ISO 2592
Total base number	7,6 mg KOH/g DIN ISO 3771
Sulfate ash	0,8 g/100g DIN 51575
Color number (ASTM)	L 2,5 DIN ISO 2049



Areas of application

Specially developed high-performance motor oil for jet ski engines. Ideally suited for sporty use thanks to the high performance of the additive package. Ideally suited for engines with or without a wet clutch. LIQUI MOLY recommends this product for manufacturers such as Honda, Kawasaki, SeaDoo, Suzuki and Yamaha.

Application

Note the engine or unit manufacturers' operating instructions.

Our information is based on thorough research and may be considered reliable, although not legally binding.