

Product information

PI 15/27/08/2020



Marine PWC Oil SAE 10W-40

Description

Fully synthetic high performance motor oil for PWCs. The special additive package ensures maximum engine performance and ideal wear protection. Guarantees the best possible lubrication, outstanding engine cleanliness and excellent friction values for wet clutches, even at high speeds. Meets or exceeds the requirements and specifications of major manufacturers.

Specifications and approvals:

API SN PLUS • JASO MA2

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Honda • Kawasaki • SeaDoo • Suzuki • Yamaha

Technical data

SAE class (engine oils)	10W-40 SAE J300
Density at 59 °F	0,860 g/cm ³ DIN 51757
Viscosity at 104 °F	96,0 mm ² /s ASTM D 7042-04
Viscosity at 212°F	14,6 mm ² /s ASTM D 7042-04
Viscosity at -13 °F (CCS)	<= 7000 mPas ASTM D 5293
Viscosity index	158 DIN ISO 2909
Pour point	-33 °F DIN ISO 3016
Evaporation loss (Noack)	10,0 % ASTM D 5800-08 Method B
Flash point	460 °F DIN ISO 2592
Total base number	7,6 mg KOH/g DIN ISO 3771
Sulfate ash	0,8 g/100g DIN 51575
Color number (ASTM)	L 2,5 DIN ISO 2049



Areas of application

For 4-stroke gasoline PWC engines with or without wet clutches, where an oil according to current product specifications is required or recommended. Safe with catalytic converters and turbochargers.

Application

Observe the manufacturers instructions!

Available pack sizes

1 l Canister plastic	20528 USA AND CANADA (-EN-F-)
4 l Canister plastic	20530 USA AND CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.