

Marine 4T Shooter

Description

Highly effective combination of cleaning and preserving additives for 4-stroke gasoline engines. Removes deposits on injection valves, intake valves, spark plugs and in the combustion chamber and prevents new deposits from forming. For a smoother running engine Eliminates starting problems and rough engine running. Preserves and protects the entire fuel system against wear, deposits and corrosion. Clean engines use less fuel and emit fewer pollutants.

Properties

- removes deposits from entire fuel system
- saves fuel and reduces pollutant emissions
- cleans the injection system
- removes carbon deposits from the intake valves and in the combustion chamber

Technical data

| | |
|---------------------|---|
| Base | Additive, spezielle Trägerflüssigkeit / additives, special liquid carrier |
| Color / appearance | hellgelb, klar / light yellow, clear |
| Form | flüssig / liquid |
| Odor | charakteristisch / characteristic |
| Density at 59 °F | 0,820 g/ml |
| Flash point | >145 °F |
| Viscosity at 104 °F | <7 mm ² /s |

Areas of application

For all types of gasoline injection systems and carburetors. For adding to fuel tanks to deal with and prevent problems.

Application

One 200 mL (6.7 FL OZ) can is sufficient for 70 liters (18 gal.) of fuel. Can be mixed with the fuel at any time. Minimum fuel filling of 50 liters (13 gal.) is requested for optimum product performance.

Comment

 **WARNING:** Cancer- www.P65Warnings.ca.gov

Available pack sizes

200 ml Can sheet metal 25102
USA (-EN-)

Our information is based on thorough research and may be considered reliable, although not legally binding.