

Top Tec ATF 1950

Description

ATF for ideal performance thanks to a premium combination of active agents. The lowered viscosity reduces consumption and increases efficiency. The outstanding stability of the friction coefficient enables extended oil change intervals.

Properties

- reduces fuel consumption
- excellent viscosity/temperature properties
- outstanding friction characteristics
- high efficiency
- very good low-temperature properties

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

MB 236.17

Technical data

Density at 15 °C	0,840 g/cm ³ DIN 51757
Viscosity at 40 °C	24,0 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	5,3 mm ² /s ASTM D 7042-04
Viscosity at -40°C (Brookfield)	<= 15000 mPas ASTM D 2983-09
Viscosity index	165 DIN ISO 2909
Pour point	-54 °C DIN ISO 3016
Flash point	180 °C DIN ISO 2592
Color / appearance	braun

Areas of application

For the new generation of the Mercedes-Benz 9-speed automatic transmissions, model 725.0/1.

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed! Do not mix with oils which have other specifications!



Available pack sizes

1 l Can plastic	21378 D-GB-I-E-P
20 l Canister plastic	21379 BOOKLET

Our information is based on thorough research and may be considered reliable, although not legally binding.