

Top Tec ATF 1950

Description

Low viscosity, synthetic based high-performance automatic transmission fluid which is specifically suitable for the use in the Mercedes-Benz 9-speed automatic transmission type 725.0/1. The composition offers maximum fuel efficiency and optimum wear protection even under extreme load.

Properties

- reduces fuel consumption
- excellent viscosity/temperature properties
- outstanding friction characteristics
- high efficiency
- very good low-temperature properties

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

MB 236.17

Technical data

Density at 59 °F	0,840 g/cm ³ DIN 51757
Viscosity at 104 °F	24,0 mm ² /s ASTM D 7042-04
Viscosity at 212°F	5,3 mm ² /s ASTM D 7042-04
Viscosity at -40 °F (Brookfield)	<= 15000 mPas ASTM D 2983-09
Viscosity index	165 DIN ISO 2909
Pour point	-65 °F DIN ISO 3016
Flash point	356 °F DIN ISO 2592
Color / appearance	braun

Areas of application

Specifically developed for the Mercedes-Benz 9-speed automatic transmission, type 725.0/1. This product is not backwards compatible with other MB specifications.

Application

Observe manufacturer's instructions.



Available pack sizes

1 l Can plastic	21378 D-GB-I-E-P
1 l Can plastic	22034 USA AND CANADA (-EN-F-)
20 l Canister plastic	21379 BOOKLET

Our information is based on thorough research and may be considered reliable, although not legally binding.