

Product information

Top Tec 6600 SAE 0W-20

PI 23/26/11/2020



Description

Fully synthetic superior low friction motor oil. The low viscosity ensures excellent cold start behavior, improves engine efficiency and reduces fuel consumption. The innovative additive technology ensures excellent protection against wear, superb engine cleanliness and greater oxidation stability. Use with extended oil change intervals as per manufacturer.

Properties

- smooth engine running
- outstanding engine cleanliness
- excellent wear protection
- high lubrication reliability
- saves fuel
- high shear stability
- optimum stability to aging
- excellent high and low temperature behavior
- for extended service intervals
- optimum oil pressure under all operating conditions
- compatible for the use with turbochargers and catalytic converters

Specifications and approvals:

ACEA C5 • API SP • ILSAC GF-6A • BMW Longlife-17 FE+ • Jaguar / Land Rover STJLR.03.5006 • MB-Approval 229.71 • Opel OV0401547

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Chrysler MS-12145 • Fiat 9.55535-GSX • Ford WSS-M2C 947-B1

Technical data

SAE class (engine oils)	0W-20 SAE J300
Density at 59 °F	0,845 g/cm ³ DIN 51757
Viscosity at 104 °F	43,0 mm ² /s ASTM D 7042-04
Viscosity at 212°F	8,50 mm ² /s ASTM D 7042-04
Viscosity at -40 °F (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -31 °F (CCS)	≤ 6200 mPas ASTM D 5293
Viscosity index	180 DIN ISO 2909

Technical data

HTHS at 302 °F	≥ 2,6 mPas ASTM D 5481
Pour point	-54 °F DIN ISO 3016
Evaporation loss (Noack)	11,0 % CEC-L-10-A-93
Flash point	446 °F DIN ISO 2592
Total base number	8,3 mg KOH/g DIN ISO 3771
Sulfate ash	≤ 0,8 % DIN 51575
Color number (ASTM)	L 3,0 DIN ISO 2049

Areas of application

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers.

Application

Observe the manufacturers instructions!

Available pack sizes

1 l Canister plastic	22044 USA AND CANADA (-EN-F-)
5 l Canister plastic	22046 USA AND CANADA (-EN-F-)
20 l Canister plastic	22048 USA AND CANADA (-EN-F-)
205 l Drum sheet metal	22049 USA AND CANADA (-EN-F-)
1000 l Container	22140 USA AND CANADA (-EN-F-)

Product information

PI 23/26/11/2020



Top Tec 6600 SAE 0W-20

Our information is based on thorough research and may be considered reliable, although not legally binding.