

Multi-disc Clutch Oil

Description

High performance gear oil specially developed for Haldex all-wheel drive, Quattro and 4motion drives. Provides excellent viscosity and shear stability as well as outstanding friction coefficient under all operating conditions. Protects reliably against wear, foaming and corrosion. Ensures optimum power transmission on all-wheel drive vehicles.



Properties

- excellent wear resistance
- excellent shear stability
- optimum friction coefficient under all operating conditions
- reliable protection against foaming
- extremely high viscosity index
- outstanding corrosion protection

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

GM • Opel • Volvo • VW G 052 175 (TL 52175) • VW G 055 175 (TL 52175-X) • VW G 060 175 (TL 52175-Y)

Available pack sizes

1 l Can plastic

22194

USA AND CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.

Technical data

Density at 59 °F	0,850 g/cm ³ DIN 51757
Viscosity at 104 °F	27,5 mm ² /s ASTM D 7042-04
Viscosity at 212°F	5,7 mm ² /s ASTM D 7042-04
Viscosity index	155 DIN ISO 2909
Pour point	-76 °F DIN ISO 3016
Flash point	446 °F DIN ISO 2592
Color / appearance	gelblich

Areas of application

For all-wheel drive systems with Haldex coupling where a fluid according to current specifications is required or recommended to use.

Application

Observe the manufacturers instructions!

Comment

 **WARNING:** Reproductive Harm - www.P65Warnings.ca.gov