

Product information

Snowmobile Motor Oil 2T Pro

PI 5/02/11/2020



Description

Part synthetic high-performance 2-stroke motor oil. Ensures optimum performance and protection of the engine in all operating conditions. Reliable lubrication, best engine cleanliness, excellent friction and minimum wear as well as low smoke.

Properties

- guarantees clean spark plugs
- burns ash-free
- self mixing
- good corrosion protection
- residue-free combustion
- very wear resistant

Specifications and approvals:

API TC • ISO L-EGC • JASO FC • TISI (Thailand International Standards Institute)

Technical data

Density at 59 °F	0,865 g/cm ³ DIN 51757
Viscosity at 104 °F	59,5 mm ² /s ASTM D 7042-04
Viscosity at 212°F	9,1 mm ² /s ASTM D 7042-04
Viscosity index	130 DIN ISO 2909
Pour point	-24°C / -11°F DIN ISO 3016
Flash point	110°C / 230°F DIN ISO 2592
Total base number	1,1 mg KOH/g DIN ISO 3771
Sulfate ash	0,06 g/100g DIN 51575
Color / appearance	rot / red

Areas of application

Particularly for air or water cooled 2-stroke engines in Snowmobiles where a motor oil according to current product specifications is required or recommended. Self-mixing. Pre-mix ratio up to 1:50 or according to manufacturers instructions.

Application

Observe the manufacturers instructions! Optimum effectiveness only when the product is used in undiluted form.



Comment

WARNING: Cancer - www.P65Warnings.ca.gov.

Available pack sizes

1 l Canister plastic	22050 USA AND CANADA (-EN-F-)
4 l Canister plastic	22052 USA AND CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.