

## Multispray PTFE

### Description

High-performance, medium-viscous multipurpose oil. Forms a highly adherent lubricant film that is very water-repellent and optimally protects all metallic components against corrosion and wear. Thanks to the large amount of specially structured PTFE, ensures the lowest friction coefficients and emergency running properties. Penetrates even hard-to-reach lubrication points through outstanding penetration properties. Guaranteed free of resins or acids.



### Properties

- maintains components in electrical systems
- excellent corrosion protection
- excellent creep properties
- increases the lubricating effect
- does not attack plastics, paints, metals and wood
- releases seized up and rusted on parts
- does not contain resins or acids

### Technical data

Form	flüssig / liquid
Base	Ölkombination / combination of oil
Color / appearance	gelblich-braun / yellowish-brown
Odor	charakteristisch / characteristic
Flash point	-10 °C
Operating temperature range	-35 - +140 °C

### Areas of application

For lubricating and preserving metal and plastic parts. For maximum protection against fretting corrosion during long-term preservation.

### Application

Spray the area to be treated and leave it to take effect.

### Available pack sizes

500 ml Can aerosol	21617 GB-E-I-P
500 ml Can aerosol	21583 DK-N-S-FIN

**Our information is based on thorough research and may be considered reliable, although not legally binding.**