# Product information
## Viscoplus for Oil

PI 43/11/12/2026



### Description
Modern, mono-functional high-performance additive for stabilizing the viscosity of motor oils. Visco Plus offers outstanding protection against mechanical and therefore permanent shear losses to the oil under extreme running conditions and is effective against the thinning of motor oils due to frequent cold starts.

### Properties
- reduces engine noise
- reduces oil consumption
- optimum oil pressure under all operating conditions
- stabilizes loss of viscosity
- optimum lubrication under all operating conditions
- fully compatible with mineral and synthetic oils
- improves the movable seal between piston and cylinder
- reduces wear

### Technical data

| | |
|---|---|
| Color / appearance | orange clear |
| Density at 20 °C | 0,89 g/cm³<br>DIN 51757 |
| Viscosity at 40 °C | 299,6 mm²/s<br>ASTM D7042 |
| Flash point | 120 °C<br>DIN ISO 2592 |
| Pour point | -15 °C<br>DIN ISO 3016 |
| Odor | characteristic |
| Form | liquid |

### Areas of application
For all cars and commercial vehicles, gasoline and diesel engines in new and used cars.

### Comment
**Not suitable for use on motorbikes with wet clutches!**

### Application
Can contents (300 ml) are sufficient for 5 liters of motor oil. After adding to the motor oil, allow the engine to run warm. The product can be added at any time.

### Available pack sizes

| | |
|---|---|
| 300 ml Can sheet metal | 1017<br>DE-FR-NL |
| 300 ml Can sheet metal | 2502<br>DE-ES-PT |
| 300 ml Can sheet metal | 2672<br>BG-DE-PL |

### Available pack sizes

| | |
|---|---|
| 300 ml Can sheet metal | 2807<br>DA-FI-NO-SV |
| 300 ml Can sheet metal | 8362<br>AR-EN-FR |
| 300 ml Can sheet metal | 8377<br>DE-HU-RO |
| 300 ml Can sheet metal | 8958<br>EL-EN-IT |
| 300 ml Can sheet metal | 20916<br>JP |
| 300 ml Can sheet metal | 21695<br>AUEN-EN |

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com