Product information Touring High Tech 20W-50

Description

Suitable for vehicles with high mileage. Mineral motor oil. Provides especially good dirtsuspending and cleaning power. Ensures the greatest lubricating film stability, ideal oil pressure and maximum wear protection even under critical conditions. For vehicles with tried and tested engine technology.

Properties

- very good dispersion properties
- tested for the use with catalytic converters
- can be used in gasoline and diesel engines with and without turbocharger
- high lubrication reliability
- prevents black sludge
- low evaporation loss
- excellent wear resistance
- excellent cleaning effect
- optimum stability to aging
- high shear stability

Specifications / Approvals

ACEA A3/B4, E2 • API SL • API CG-4 • Allison C4 • MIL-L 2104 E

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

Caterpillar TO-2 • MAN 271 • MB 228.3

Technical data

SAE class (engine oils)	20W-50 SAE J300
Density at 15 °C	0,880 g/cm³ DIN 51757
Viscosity at 40 °C	165,0 mm²/s ASTM D 7042-04
Viscosity at 100 °C	18,5 mm²/s ASTM D 7042-04
Viscosity at -20 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -15 °C (CCS)	≤ 9500 mPas ASTM D5293
Viscosity index	125 DIN ISO 2909
HTHS at 150°C	≥ 3,7 mPas ASTM D5481
Pour point	-30 °C DIN ISO 3016
Evaporation loss (Noack)	7,2 % CEC-L-40-A-93

Total base number
Sulfate ash

Color number (ASTM)

Areas of application

All-year oil for gasoline and diesel engines. Can be used on all vehicles without diesel particulate filters also in mixed fleets. Tested safe with catalytic converters and turbochargers.

Application

The operating instructions of the vehicle and engine manufacturers must be followed.

Available pack sizes

1 l Canister plastic	20812 BOOKLET
4 l Canister plastic	2568 BOOKLET
5 l Canister plastic	20813 BOOKLET
5 l Canister plastic	21250 ALGERIEN-GB-ARAB-F
20 l Canister plastic	1257 D-GB
60 l Black plate barrel	1254 D-GB
205 l Black plate barrel	1260 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.





20W-50

230 °C

DIN ISO 2592

DIN ISO 3771

DIN ISO 2049

DIN 51575

15.5

10,2 mg KOH/g

1,0 - 1,6 g/100g

PI 52/04/25/2023