Product information
Saw Chain Oil 100

PI 29/08/12/2026



Description
Mineral-based high-performance oil for once-through loss lubrication. Thanks to the outstanding adhesion properties and first-class lubricating effect, provides optimum protection of moving parts such as chain links and joints against wear and corrosion. Ensures year-round use at all outside temperatures based on its favorable viscosity characteristics.

Properties
- excellent low temperature behavior
- outstanding lubricating action
- outstandingly adherent
- excellent viscosity/temperature properties

Technical data

ISO viscosity class	100 DIN 51519
Density at 15 °C	0,87 g/cm³ DIN 51757
Viscosity at 40 °C	100 mm²/s ASTM D 7042-04
Viscosity at 100 °C	13,2 mm²/s ASTM D 7042-04
Viscosity index	130 DIN ISO 2909
Pour point	-39 °C DIN ISO 3016
Flash point	220 °C DIN ISO 2592
Oxide ash	0,5 g/100g DIN EN ISO 6245
Color / appearance	grau-schwarz

Areas of application

For lubricating chains on chainsaws, reciprocating saws, etc. Also suitable for extreme applications such as sawing hardwoods.

⚠ 0

Application

The specifications and instructions from the unit or chain manufacturer must be followed.

Available pack sizes

1 l Canister plastic	1277 AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH

Available pack sizes

5 l Canister plastic	1278 AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
60 l Black plate barrel	1191 DE-EN-ES-FR-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com