Product information

PI 53/11/13/2026

Synthoil Race Tech GT1 10W-60



Description

Fully synthetic high-performance motor oil for extreme operating conditions. With wide-band viscosity 10W-60 and high temperature stability. Optimizes engine performance. For immediate lubrication at cold start and very good wear protection.

Properties

- outstanding engine cleanliness
- miscible with all commercially available motor oils
- optimum stability to aging
- instant lubrication after cold start
- high lubrication reliability
- optimum lubrication in extreme operating conditions
- tested for the use with catalytic converters
- extremely low evaporation loss
- extremely low oil consumption

Specifications / Approvals

ACEA A3 • ACEA B4 • API SN

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

Fiat 9.55535-H3

Technical data

SAE class (engine oils)	10W-60 SAE J300
Density at 15 °C	0,855 g/cm³ DIN 51757
Viscosity at 40 °C	180,0 mm²/s ASTM D7042
Viscosity at 100 °C	25,0 mm²/s ASTM D7042
Viscosity at -30 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -25 °C (CCS)	⩽ 7000 mPas ASTM D5293
Viscosity index	175 DIN ISO 2909
HTHS at 150°C	⩾ 3,7 mPas ASTM D5481
Pour point	-36 °C DIN ISO 3016
Evaporation loss (Noack)	5,0 % CEC-L-40-A-93
Flash point	240 °C DIN ISO 2592
Total base number	10,5 mg KOH/g DIN ISO 3771

Technical data

Sulfate ash	1,0 - 1,6 g/100g DIN 51575
Color number (ASTM)	L3,0 DIN ISO 2049

Areas of application

For gasoline and diesel engines with and without turbocharging. Especially suitable for extreme engine requirements and racing.

Application

Note the vehicle and engine manufacturers' operating instructions.

Available pack sizes

1 l Canister plastic	8908 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
1 l Canister plastic	20911 JA
5 l Canister plastic	8909 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
5 l Canister plastic	20912 JA
20 l Canister plastic	1392 DE-EN-ES-IT-PT
60 l Black plate barrel	1393 DE-EN-ES-FR-IT-PT
205 l Black plate barrel	1394 DE-EN-ES-FR-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com