Product information
Special Bulldog Oil SAE 30

PI 24/08/25/2026



Description

Special Bulldog Oil is manufactured using a modified process. This refined product is especially suitable for lubrication in 2-stroke internal combustion power engines with hot bulb and loss lubrication.

Properties

- outstanding lubrication reliability
- guarantees optimum combustion
- mineral based
- low flash point
- low pour point
- unblended
- prevents oil smuts

Technical data

ISO viscosity class	VG 100 DIN 51519
Density at 15 °C	0,865 g/cm³ DIN 51757
Viscosity at 40 °C	100,0 mm²/s ASTM D7042
Viscosity at 100 °C	11,0 mm²/s ASTM 7042
Viscosity index	95 DIN ISO 2909
Pour point	-18 °C DIN ISO 3016
Flash point	256 °C DIN ISO 2592
Oxide ash	<0,01 g/100g DIN EN ISO 6245
Increase in coke residues	0,9 % DIN 51352 Blatt 1
Initial boiling point	410 °C ASTM D1160
Color number (ASTM)	L 1,0 DIN ISO 2049
suitable for flow temperatures up to	320 °C
maximum permitted film temperature	340 °C

Areas of application

Specially developed for Lanz Bulldog 2-stroke engines with hot bulb and loss lubrication. Not suitable for four-stroke engines requiring blended oils or oils with additives.

Application

The operating instructions of the machine manufacturers must be followed.

Available pack sizes

10 l Canister plastic	1400 DE-EN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com