Product information

PI 36/10/30/2026

Motorbike 2T Synth Street Race

Description



Fully synthetic high-performance motor oil. Ensures maximum performance, lubrication, wear protection and engine cleanliness under all operating conditions. Offers excellent friction characteristics, significantly enhancing driving pleasure. Tested for catalytic converters. Tested on racing machines.

Properties

- high wear resistance
- high thermal stability
- good corrosion protection
- self mixing
- residue-free combustion
- prevents the build-up of deposits

Specifications / Approvals

API TC • Husqvarna • ISO L-EGD • JASO FD

Technical data

Density at 15 °C	0,875 g/cm³ DIN 51757
Viscosity at 40 °C	50 mm²/s ASTM D 7042-04
Viscosity at 100 °C	9,1 mm²/s ASTM D 7042-04
Viscosity index	165 DIN ISO 2909
Pour point	-48 °C DIN ISO 3016
Flash point	98 °C DIN ISO 2592
Total base number	2,3 mg KOH/g DIN ISO 3771
Sulfate ash	0,15 g/100g DIN 51575
Color / appearance	red

Areas of application

For separate and mixture lubrication systems in air- and water-cooled 2-stroke engines. Specifically for sporting applications. Self-mixing. Mixture ratio up to 1:100 according to the manufacturer's instructions.

Application

For mixture lubrication, pour the contents of the can into the fuel tank and top up the fuel according to the mixing ratio. Mixing takes place automatically. For separate lubrication, pour the contents of the can into the oil tank. Oil is mixed with fuel via the metering device.

Available pack sizes

1 l Canister plastic	1505 AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
20 l Canister plastic	1566 DE-EN-ES-FR-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com