

Motorbike Fork Oil 15W heavy

Description

Full synthetic fork oil and shock-absorber oil. Has been developed for universal use. Special synthetic base oils and corresponding additives guarantee optimum driveability and damping. Prevents foam formation and seal hardening. Good corrosion and wear protection provide long service life.

Properties

- high wear resistance
- prevents foam formation
- increases driving safety
- lasting corrosion protection
- prevents seals from swelling

Technical data

| | |
|---------------------|---|
| Density at 15 °C | 0,835 g/cm ³ DIN 51757 |
| Viscosity at 40 °C | 45 mm ² /s ASTM D 7042-04 |
| Viscosity at 100 °C | 8 mm ² /s ASTM D 7042-04 |
| Viscosity index | 151 DIN ISO 2909 |
| Pour point | -36 °C DIN ISO 3016 |
| Flash point | 260 °C DIN ISO 2592 |
| Color number (ASTM) | L 0,5 DIN ISO 2049 |

Areas of application

Universal use in telescopic forks, shock absorbers in motorcycles, motor bicycles, mopeds and other two-wheeled vehicles.

Application

Follow the instructions of the telescopic fork, shock absorber and two-wheel vehicle manufacturers.

Available pack sizes

| | |
|--------------------|--------------------|
| 500 ml Can plastic | 1524 D-GB-I-E-P |
| 500 ml Can plastic | 5954 D-F-I-GR |
| 1 l Can plastic | 2717 D-GB-I-E-P |

Our information is based on thorough research and may be considered reliable, although not legally binding.

