Product information

PI 36/09/15/2026

Motorbike 2T Bike-Additive



Description

Increases the performance of the engine. Removes deposits in the fuel system as well as at intake and exhaust ports and prevents new deposits from forming. Protects the entire fuel system against corrosion. Tested on engines with catalytic converters. Clean engines use less fuel and reduce the pollutant emissions.

Properties

- increases operational reliability
- highly economical
- optimizes engine performance
- tested for the use with catalytic converters
- cleans carburetors
- reduces residue
- prevents corrosion in the fuel system

Technical data

Form	liquid
Color / appearance	yellow
Odor	characteristic
Density at 20 °C	0,806 g/ml
Flash point	>61 °C
Shelf life in original sealed container	60 months

Areas of application

For all 2-stroke engines with mixture or separate lubrication.

Application

Filling the dosage chamber (25 ml) once is sufficient for 5 l of fuel or fuel mixture.

Available pack sizes

250 ml Dispensing bottle plastic	1582 DE-EN-ES-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com