

Description

White, fully-synthetic special grease. For maximum lubrication through visible application to chain. Cold, heat and spray-water resistant. Very good adhesion properties and wear protection. Reduces chain elongation and extends the chain's service life. Excellent penetration properties and excellent corrosion protection. It is possible to refill the 50 ml can from the 400 ml can.

Properties

- excellent penetration action
- especially cold, hot and splash-water resistant
- outstanding corrosion protection
- excellent adhesion
- friction and wear reducing
- resistant to acceleration forces
- highest load-carrying capacity
- reduces chain elongation

Technical data

Base	synthetic oil, additives
Color / appearance	white
Operating temperature	-30 to +180 °C
range	
missing translation	short term 200 °C °C
Water resistance at 90 °C	0
	DIN 51 807
Form	aerosol, liquid
Odor	characteristic

Areas of application

For all high-load and fast-running motorcycle chains with and without O-rings and X-rings.

Application

Before use we recommend cleaning the chain with Motorbike Chain and Brake Cleaner (part no. 1602). Spray chain with Motorbike Chain Spray White. The lubricant attains its final consistency and adherence once the solvent has evaporated.

Available pack sizes

50 ml Can aerosol	1592 D-GB
400 ml Can aerosol	1591 D-GB-E-P
400 ml Can aerosol	5981 D-F-I-NL



Our information is based on thorough research and may be considered reliable, although not legally binding.