Product information
MoS2-Rust Solvent

PI 27/09/25/2026



Description
Excellent lubricant for all moving parts. Penetrates even the tightest fits and infiltrates and dissolves rust. Prevents squeaking noises, corrosion as well as oxidation and keeps moving parts permanently smooth-running. Penetrates quickly and is neutral to most paints, metals, plastics and elastomers. Displaces water and ensures low friction values thanks to MoS2 solid lubricant.

Properties
- good water resistance
- good corrosion protection
- low coefficient of friction
- dissolves rust
- releases dirt
- penetrtes fast

Technical data

Base	combination of oils, agents and MoS2 solid
Color / appearance	grey
Spreading rate (cover)	sheet steel, bright 140-180 m²/l
Operating temperature range	-40 bis +140 °C
Odor	characteristic
Form	aerosol, liquid

Areas of application
For a wide range of applications and devices in the factory, workshop, automotive as well as household and hobby.

Application
Spray a generous amount onto bolts or nuts to be loosened and as is usual with rust removers, allow to act for some time before loosening, depending on the corrosion formation. Repeat the process in extreme cases.

Available pack sizes

300 ml Can aerosol	1614 DE-EN-ES-IT-PT
300 ml Can aerosol	1817 DE-FR-NL
300 ml Can aerosol	2694 HU-PL-RO-TR
600 ml Can aerosol	1613 DE-EN-ES-IT-PT
600 ml Can aerosol	2653 HU-PL-RO-TR

Available pack sizes

600 ml Can aerosol	2993 DA-EN-FI-NO-SV

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com