

Motorbike Gear Oil (GL4) 80W

Description

Mineral-based transmission oil of API GL-4 performance class based on selected base oils and additives. Ensures easy, precise shifting operations.

Properties

- excellent resistance to aging
- excellent viscosity/temperature properties
- high wear resistance
- does not attack common sealing materials
- reduces running noise
- high pressure-absorption capability



Our information is based on thorough research and may be considered reliable, although not legally binding.

Specifications / Approvals

API GL4 • MIL-L 2105 • ZF TE-ML 02B • ZF TE-ML 17A

Technical data

SAE class (gear oils)	80W SAE J306
Density at 15 °C	0,88 g/cm ³ DIN 51757
Viscosity at 40 °C	93,4 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	11,4 mm ² /s ASTM D 7042-04
Viscosity at -26 °C (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	110 DIN ISO 2909
Pour point	-27 °C DIN ISO 3016
Flash point	218 °C DIN ISO 2592
Color number (ASTM)	3,5 DIN ISO 2049

Areas of application

For transmissions and final drives operating under high load. Note the transmission manufacturer's instructions.

Application

Note the transmission manufacturer's instructions. Mixable with all branded gear oils. Optimum effect only when the product is used unmixed.

Available pack sizes

500 ml Can plastic	1617 D-GB-I-E-P
500 ml Can plastic	5928 D-F-I-GR