

Product information

megol Motorenoel SHPD SAE 15W-40



Description

Super high-performance diesel motor oil. Approved for extended oil change intervals in accordance with the recommendations of commercial vehicle manufacturers. Multigrade oil with the highest power reserve, allowing full use to be made of the maximal oil change intervals of up to 45,000 km according to the maintenance system of the respective engine manufacturers. Thanks to its high-quality base oils and perfectly tailored additive packages, offers a wide range of applications and guarantees optimum engine running and wear protection.

Range of applications: Trucks, construction and agricultural machinery.

SAPS level: High-SAPS.

Note the manufacturer's instructions!

Specifications / Approvals

ACEA A3/B4, E7 • API SL • API CH-4 • DTFR 15B110 [228.3] • Mack EO-M Plus • Renault Trucks RD-2 • Volvo VDS-2

Meguin also recommends this product for vehicles that are subject to the following specifications

Cummins CES 20076 • Cummins CES 20077 • MAN M 3275-1 • MTU Typ 2

Characteristic data

SAE class (engine oils)	15W-40 SAE J300
Density at 15 °C	0,875 g/cm ³ DIN 51757
Viscosity at 40 °C	105 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,5 mm ² /s ASTM D 7042-04
Viscosity at -25 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -20 °C (CCS)	<= 7000 mPas ASTM D5293
Viscosity index	142 DIN ISO 2909
HTHS at 150°C	>= 3,7 mPas ASTM D5481
Pour point	-36 °C DIN ISO 3016
Evaporation loss (Noack)	11,7 % CEC-L-40-A-93

Characteristic data

Flash point	228 °C DIN ISO 2592
Total base number	9,7 mg KOH/g DIN ISO 3771
Sulfate ash	1,0 - 1,6 g/100g DIN 51575
Color number (ASTM)	L4,5 DIN ISO 2049

Available pack sizes

5 l Canister plastic	1678 D-GB-F-ARAB-RUS-RO-I-E-P
20 l Canister plastic	1674 D-GB
60 l Black plate barrel	1675 D-GB
200 l Black plate barrel	1676 D-GB
1.000 l Deposit container	9757 D-GB
1 l Bulk goods	1677 D
1 l Tank truck	3527 D