Product information
Super Diesel Additive

PI 74/11/12/2026



Description
Combination of active ingredients with cleaning, dispersing, material-protecting, and cetane-boosting properties. Contains a lubricity improver that provides low-sulfur diesel fuels with sufficient lubricity. By improving ignition quality, the fuel burns more efficiently when the engine is cold.

Properties
- keeps injection nozzles clean
- good corrosion protection
- tested for the use with catalytic converters
- prevents the build-up of deposits
- prevents seizing and the injector needles from gumming up
- excellent cleanliness
- boosts the cetane number
- high wear resistance
- keeps the fuel system clean
- for low-sulfur diesel fuels
- increases the lubricating effect

Technical data

Base	additive mixture in liquid carrier
Color / appearance	light brown, clear
Regulation on Flammable Liquids Class (Germany)	A III
Flash point	63 °C
Pour point	-36 °C
Form	liquid
Odor	characteristic

Areas of application
Add to diesel fuel for all diesel engines, especially modern high-pressure diesel engines in passenger cars, trucks, tractors, construction equipment, and stationary engines. Excellent for preserving engines during extended periods of shutdown under extreme conditions. Turbocharger tested. Suitable for HVO and XTL diesel fuels.

Application

Continuous use of the product in low-sulfur diesel fuels increases the cetane number and improves lubricity. One 250 ml dose is sufficient to treat 75 L of diesel fuel. Dosage: 1:300.

Keeps injectors clean and provides corrosion protection when added to the diesel fuel every 2,000 km.

5 L canisters and 50 L drums for trucks, freight companies, bus companies, and industrial applications. Add to diesel fuel at a ratio of 1:300.

When shutting down and preserving engines, add to the diesel fuel at a rate of 1%. Follow the preservation instructions.

Can be mixed with fuel at any time since mixing takes place automatically.

Available pack sizes

250 ml Can sheet metal	1806 EL-EN-IT
250 ml Can sheet metal	2504 DE-ES-PT
250 ml Can sheet metal	2814 DA-FI-NO-SV
250 ml Can sheet metal	5120 DE-FR-NL
250 ml Can sheet metal	7130 AR-DZAR-EN-FR
250 ml Can sheet metal	8343 BG-DE-PL
250 ml Can sheet metal	8366 AR-EN-FR
250 ml Can sheet metal	8379 DE-HU-RO
250 ml Can sheet metal	20692 DE-EN-ZH
250 ml Can sheet metal	20807 DE-EN-HR-SL-SR
250 ml Can sheet metal	20868 JA
250 ml Can sheet metal	21506 DE-FR
300 ml Can sheet metal	2904 EN-HE
5 l Canister plastic	5140 DE-EN
50 l Black plate barrel	5145 DE-EN

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com

Product information

Super Diesel Additive

PI 74/11/12/2026

Available pack sizes

205 l Black plate barrel	5146
	DE-EN-ES-FR-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com