

Leak Finder Spray

Description

Leak test fluid for detecting spots where gas and compressed air may escape. Locates leaks on tanks, pipes, hoses, screw joints, welding seams, flange connections and fittings. Water-soluble and biodegradable test fluid filled with environmentally friendly propellant. The high bubble formation guarantees economic and reliable use.

Properties

- biologically degradable
- environmentally friendly
- miscible with water
- high capacity
- forms air bubbles

Technical data

Compatibility with plastics, resistance to stress cracking	Not compatible with all plastics. Crack formation possible with polyamide (stress-corrosion cracking)
Compatibility with materials (seals)	compatible DIN 30660
Compatibility with materials (lubricants)	compatible DIN 3536
Active agent content	>98,5 %
Foam stability	~ 80 %
Compatibility with materials (PE pipes)	compatible DIN 30657
Corrosion according to DIN 30660	no corrosion on iron, zinc, tin, copper, brass and aluminium
Odor	slightly
Form	aerosol liquid
Color / appearance	colourless
pH value	6-7,5
Shelf life in original sealed container	24 months

Areas of application

Motor vehicle maintenance:
For repair work on pneumatic brake systems and air conditioning units in trucks, cars and commercial vehicles. For locating leaks on tires, hoses and welding equipment.

Industry:
Test and maintenance work on compressed air and all gas lines including oxygen.



Medicine:

For testing operating room fittings for anesthetic apparatus and resuscitating equipment.

Household and sport:

Domestic and municipal gas lines, diving equipment and camping equipment.

Approvals: DVGW tested, DIN-DVGW reg. no. NG-5170A00659

Application

Spray an appropriate amount onto the components to be tested.

Available pack sizes

400 ml Can aerosol	1809 D-NL-F-GR-ARAB
400 ml Can aerosol	2836 GB-DK-FIN-N-S
400 ml Can aerosol	3350 D-GB-I-E-P

Our information is based on thorough research and may be considered reliable, although not legally binding.